PRELIMINARY

SMBB1550-3100S-I
High Power Top LED

<Specifications>

1. Product Name: High Power Top LED
2. Type Number: SMBB1550-3100S-I
3. Chip:
   - Chip material: InGaAs/InP
   - Chip Dimension: 1000umx1000um
   - Chip Number: 3pcs
   - Peak Wavelength: 1550nm typ.
4. Package
   - Lead Frame Die: Silver Plated on Copper
   - Package Resin: PA9T Resin
   - Lens: Silicone Resin

Outer Dimension (Unit:mm)



Absolute Maximum Ratings[Tc=25℃]			
Item	Symbol	Maximum Rated Value	Unit
Power Dissipation	PD	3000	mW
Forward Current	IF	700	mA
Pulse Forward Current*	IFP	2000	mA
Reverse Voltage	VR	15	V
Thermal Resistance	Rthja	10	K/W
Junction Temperature	Tj	120	℃
Operating Temperature	TOPR	-40 ~ +100	℃
Storage Temperature	TSTG	-40 ~ +100	℃
Soldering Temperature**	TSOL	250	℃

* Duty=1% and Pulse Width=10μs.
** Soldering condition must be completed within 5 second at 250 ℃.

Electro-Optical Characteristics [Tc=25℃ typ.]						
Item	Symbol	Condition	Minimum	Typical	Maximum	Unit
Forward Voltage	VF	IF=500mA		3.2	4.2	V
	VFP	IFP=2A		5.1		
Radiated Power*	PO	IF=500mA		(40)		mW
		IFP=2A		(80)		
Peak Wavelength	λP	IF=500mA	1500		1600	nm
Half Width	Δλ	IF=500mA		120		nm
Viewing Half Angle	θ1/2	IF=100mA		-		deg
Rise Time	tr	IF=500mA		90		ns
Fall Time	tf	IF=500mA		50		ns

* Measured by G8370-85

RoHS Compliant

Typical Characteristic Curves

Forward Curent - Forward Voltage



Relative Radiant Intensity - Forward Current



Forward Current - Pulse Duration



Allowable Forward Current - Ambient Temperature




Forward Voltage -
Ambient Temperture
If=500mA
Forward Voltage (V)
3.5
3.4
3.3
3.2
3.1
3.0
2.9
2.8
2.7
2.6
2.5
0
20
40
60
80
100
Ambient Temperatture (°C)


Relative Radiant Intensity -
Ambient Temperature
If=500mA
Relative Radiant Intensity (A.U.)
10
1
0.1
0
20
40
60
80
100
Ambient Temperature (°C)


Peak Wavelength -
Ambient Temperature
If=500mA
Peak Wavelength (nm)
1600
1590
1580
1570
1560
1550
1540
1530
1520
1510
1500
0
20
40
60
80
100
Ambient Temperature (°C)


Relative Spectral Emission
(ta=25°C)
Relative Radiant Intensity (A.U.)
1.0
0.9
0.8
0.7
0.6
0.5
0.4
0.3
0.2
0.1
0.0
1300
1400
1500
1600
Wavelength (nm)

Wrapping

Moisture barrier bag aluminum laminated film with a desiccant to keep out the moisture absorption during the transportation and storage.

SMD LED storage and handling precautions

Storage Conditions before Opening a Moisture-Barrier Aluminum Bag

- Before opening a moisture-barrier aluminum bag, please store it at <30ºC, <60%RH.
- Please note that the maximum shelf life is 12 months under these conditions.

Storage Conditions after Opening a Moisture-Barrier Aluminum Bag

- After opening a moisture-barrier aluminum bag, store the aluminum bag and silica gel in a desiccator.
- After opening the bag, please solder the LEDs within 72 hours in a room with 5 - 30ºC, <50%RH.
- Please put any unused, remaining LEDs and silica gel back in the same aluminum bag and then vacuum-seal the bag.
- It is recommended to keep the re-sealed bag in a desiccator at <30%RH.

- The 72-hour- long floor life does not include the time while LEDs are stored in the moisture-barrier aluminum bag. However, we strongly recommend to solder the LEDs as soon as possible after opening the aluminum bag

Notes about Re-sealing a Moisture-Barrier Aluminum Bag

- When vacuum-sealing an opened aluminum bag, if you find the moisture-indicator of the silica gel has changed to pink from blue (indicating a relative humidity of 30 % or more), please do not use the unused LEDs, the aluminum bag, or the silica gel.

Notes about Opening a Re-sealed Moisture-Barrier Aluminum Bag

- When opening a vacuumed and re-sealed aluminum bag in order to use the remaining LEDs stored in the bag, if you find that the moisture-indicator of the silica has changed to pink, please do not use the LEDs.

Disclaimer

Product specifications and data shown in this product catalog are subject to change without notice for the purposes of improving product performance, reliability, design, or otherwise.

Product data and parameters in this catalog are typical values based on reasonably up-to-date measurements. Product data and parameters may vary by user application and over time.

Products shown in this catalog are intended to be used for general electronic equipment. Products are not guaranteed for applications where product malfunction or failure may cause personal injury or death, including but not limited to life-supporting / saving devices, medical devices, safety devices, airplanes, aerospace equipment, automobiles, traffic control systems, and nuclear reactor control systems.

2016.01