

SMT660N


High Performance Red Color TOP LED

SMT660N consists of an AlGaInP LED mounted on the lead frame as TOP LED package. It is 31mW typical of output power and 750mcd of Brightness. It emits a spectral band of radiation at 660nm.

<Specifications>

1. Product Name: TOP LED
2. Type Number: SMT660N
3. Chip:
 - Chip Material: AlGaInP
 - Dimension: 0.35mm x 0.35mm
 - Peak Wavelength: 660nm
4. Package
 - Lead Frame Die: Silver Plated
 - Package Resin: PPA Resin
 - Lens: Epoxy Resin

Outer Dimension (Unit:mm)



Absolute Maximum Ratings[Ta=25°C]			
Item	Symbol	Maximum Rated Value	Unit
Power Dissipation	PD	120	mW
Pulse Forward Current*	IF	50	mA
Reverse Voltage	VR	5	V
Operating Temperature	TOPR	-20 ~ +80	°C
Storage Temperature	TSTG	-30 ~ +80	°C
Soldering Temperature**	TSOL	255	°C

* Duty=1% and Pulse Width=10us.

** Soldering condition must be completed within 10 second at 255°C.

Electro-Optical Characteristics [Ta=25°C]						
Item	Symbol	Condition	Minimum	Typical	Maximum	Unit
Forward Voltage	VF	IF=20mA		2.0	2.2	V
	VFP	IF=50mA		2.2	2.4	
Total Radiated Power*	PO	IF=20mA	9	12		mW
		IF=50mA		31		
Radiant Intensity**	IE	IF=20mA		4		mW/sr
		IF=50mA		11		
Brightness	IV	IF=20mA		300		mcd
		IF=50mA		750		
Peak Wavelength	λP	IF=50mA	650	660	660	nm
Half Width	Δλ	IF=50mA		16		nm
Viewing Half Angle	θ1/2	IF=50mA		±63		deg



* Measured by Photodyne #500

** Measured by Tektronix J-6512




◆ SMD Application
IR-Reflow Soldering Profile for lead free soldering

recommended Land Layout (Unit: mm)



Don't put stress on SMD and a circuit board after soldering.

◆ SMD Packing
Tape and Reel Dimensions (Unit: mm)



Feeding Direction -->

◆ Wrapping

Moisture barrier bag aluminum laminated film with a desiccant to keep out the moisture absorption during the transportation and storage.

SMD LED STORAGE AND HANDLING PRECAUTIONS

<Storage Conditions before Opening a Moisture-Barrier Aluminum Bag>

- Before opening a moisture-barrier aluminum bag, please store it at <30°C, <60%RH. Please note that the maximum shelf life is 12 months under these conditions.

<Storage Conditions after Opening a Moisture-Barrier Aluminum Bag>

- After opening a moisture-barrier aluminum bag, store the aluminum bag and silica gel in a desiccator.
- After opening the bag, please solder the LEDs within 48 hours in a room with 5 - 30°C, <50%RH.
- Please put any unused, remaining LEDs and silica gel back in the same aluminum bag and then vacuum-seal the bag.
- It is recommended to keep the re-sealed bag in a desiccator at <30%RH.

<Notes about Re-sealing a Moisture-Barrier Aluminum Bag>

- When vacuum-sealing an opened aluminum bag, if you find the moisture-indicator of the silica gel has changed to pink from blue (indicating a relative humidity of 30 % or more), please do not use the unused LEDs, the aluminum bag, or the silica gel.

<Notes about Opening a Re-sealed Moisture-Barrier Aluminum Bag>

- When opening a vacuumed and re-sealed aluminum bag in order to use the remaining LEDs stored in the bag, if you find that the moisture-indicator of the silica has changed to pink, please do not use the LEDs.

※ The 48-hour- long floor life does not include the time while LEDs are stored in the moisture-barrier aluminum bag.
However, we strongly recommend to solder the LEDs as soon as possible after opening the aluminum bag.