


L1550-35M32
Infrared LED

<Specifications>

- Ship Material: InGaAsP
- Chip Dimension: 300um x 300um
- Number of Chips: 1piece
- Peak Wavelength: 1550nm typ.
- Stem: TO-18 type
- Lens: Glass Ball Lens
- CAP: Gold Plated



Absolute Maximum Ratings[Ta=25°C]			
Item	Symbol	Maximum Rated Value	Unit
Power Dissipation	PD	130	mW
Forward Current	IF	100	mA
Pulse Forward Current*	IFP	1000	mA
Reverse Voltage	VR	5	V
Junction Temperature	Tj	120	°C
Thermal Resistance	Rthja	300	K/W
Operating Temperature	TOPR	-40 ~ +100	°C
Storage Temperature	TSTG	-40 ~ +100	°C
Soldering Temperature **	TSOL	250	°C

* Duty=1% and Pulse Width=10μs.




** Soldering condition must be completed within 5 second at 250°C. and is allowed in the area apart 3mm from the bottom of the lamp.

Electro-Optical Characteristics[Tc=25°C]						
Item	Symbol	Condition	Min	Typ	Max	Unit
Forward Voltage	VF	IF=50mA		0.9	1.3	V
	VFP	IPF=1A		1.7		
Total Radiated Power*	PO	IF=50mA		1.8		mW
		IPF=1A		10		
Radiant Intensity**	IE	IF=50mA		22		mW/sr
		IPF=1A		120		
Peak Wavelength	λP	IF=50mA	1500		1600	nm
Half Width	Δλ	IF=50mA		120		nm
Viewing Half Angle	θ1/2	IF=50mA		±14		deg
Rise Time	tr	IF=50mA		30		ns
Fall Time	tf	IF=50mA		70		ns


* Measured by G8370-85

** Measured by Ando Optical Multi Meter AQ2140&AQ2742







Relative Spectral Emission



Radiation Characteristics



Radiation Characteristics



Disclaimer

Product specifications and data shown in this product catalog are subject to change without notice for the purposes of improving product performance, reliability, design, or otherwise.

Product data and parameters in this catalog are typical values based on reasonably up-to-date measurements.

Product data and parameters may vary by user application and over time.

Products shown in this catalog are intended to be used for general electronic equipment. Products are not guaranteed for applications where product malfunction or failure may cause personal injury or death, including but not limited to life-supporting / saving devices, medical devices, safety devices, airplanes, aerospace equipment, automobiles, traffic control systems, and nuclear reactor control systems.

2018.08